

CMI BETAPLAS PMP CLAY



DESCRIPTION

CMI BetaPlas PMP Clay is a ready to use plasticizing powder additives added into plaster and mortar mixes to increase its workability and adhesion strength and at the same time minimizes shrinkage and cracks. It is specially formulated as a superior alternative to lime putty or slaked lime for cementitious mixes at site. It conforms to BS 4887: 1973 and is suitable for use in interior and exterior areas such as general purpose repair mortar, wall plastering, floor screeds and masonry mortar for laying brick and blockwalls.

USES

- · Additives for repair mortar
- · Additives for rendering and screeding
- · Additives for masonry mortar

TECHNICAL DATA

Colour : Off-White

Additives : Water-soluble polymeric fibres for

improved workability and strength

pH : 8.5

Aggregate size : Max. 0.5 mm

Pot Life : Approx. 1 hours after addition

SURFACE PREPARATION

Remove all traces of dirt, dust, grease and foreign materials from substrate. It is recommended to apply a key bonding coat for soffit and sheer wall concrete surfaces for thick plastering.

MIXING

Plastering Mortar : 150 gm sachet : 50 kg OPC : 150 – 200 kg washed sand Masonry Mortar : 150 gm sachet : 50 kg OPC : 250 – 300 kg washed sand Screeding Mortar : 150 gm sachet : 50 kg OPC : 350 – 400 kg washed sand

Prepare mortar mix as per above recommendation by sprinkled CMI BetaPlas PMP Clay over the mixture. Whilst mixing, add water slowly to the required consistency. Mix thoroughly until a lump-free homogenous paste is achieved. The mix is now ready for use.

PACKAGING

150 gm / sachet. 60 sachets per carton.

SHELF LIFE & STORAGE

12 months when stored in cool and dry place

CMI CONSTRUCTION MATERIAL INDUSTRY SDN BHD (422436-0)

No. 7, Jalan Sungai Jerluh 32/196, Bukit Kemuning Section 32, 40460 Shah Alam, Selangor. Tel: 603-5131 9325 / 9425 Fax: 603-5131 8325 Email: enquiry@cmimalaysia.com.my www.cmimalaysia.com.my



Delivering Dry-Mix Solutions